

Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 001 329 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
17.05.2000 Bulletin 2000/20

(51) Int. Cl.⁷: G06F 1/00

(21) Application number: 99120094.0

(22) Date of filing: 21.10.1999

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 10.11.1998 US 189960
05.10.1999 US 412292

(71) Applicant:
Aladdin Knowledge Systems Ltd.
Tel Aviv 67211 (IL)

(72) Inventors:
• Margalit, Yanki
Ramat Gan 52223 (IL)
• Margalit, Dany
Ramat Gan 52223 (IL)
• Kastershtien, Rami
Tel Aviv 67442 (IL)

(74) Representative:
Modiano, Guido, Dr.-Ing. et al
Modiano, Josef, Pisanty & Staub,
Baaderstrasse 3
80469 München (DE)

(54) A user-computer interaction method for use by flexibly connectable computer systems

(57) A user-computer interaction method for use by a population of flexibly connectable computer systems and a population of mobile users, the method comprising storing information characterizing each mobile user on an FCCS plug to be borne by that mobile user; and accepting the FCCS plug from the mobile user for connection to one of the flexibly connectable computer systems and employing the information characterizing the mobile user to perform at least one computer operation.

FIG. 1





FIG. 5B



EP 1 001 329 A2

Description

FIELD OF THE INVENTION

[0001] The present invention relates to flexibly connectible computer apparatus and methods for using flexibly connectible hosts.

BACKGROUND OF THE INVENTION

[0002] The USB interface is described in specifications available over the Internet at www.usb.org.

[0003] Firewire technology, also termed "IEEE 1394 technology", is an alternative to USB which also provides flexible connectivity and is described in the IEEE 1394 standard.

[0004] USBHasp is an Aladdin software protection product, announced in October 1997, which includes a USB key. USBHasp does not control access of a user to a computer network but rather impedes interaction between software and a computer system by activating a copy of the software only if a USB key corresponding to that copy is plugged into the computer system.

[0005] Conventionally, the only devices which have interacted via USB have been computers, keyboard, monitor, printer, mouse, smart card readers, and biometric readers.

[0006] Conventional devices for providing computerized servicing to a mobile or stationary population of users typically include a smart card reader. The members of the mobile population bear smart cards which are used to interact with the computerized servicing device via the smart card reader.

[0007] A particular disadvantage of smart cards is that they require a smart card reader which is a relatively costly device. Computer hosts which are equipped with a smart card reader are a small subset of the universe of computer hosts because addition of a smart card reader makes the computer considerably more expensive.

[0008] German Patent document DE 19631050 describes an interface converter for a universal serial bus having a module with a processor that changes format and protocol into that of a different bus system.

[0009] Rainbow Technologies, Inc., in a news release dated 17 November 1998, announce USB software protection keys which can also be used as authentication or access control devices. A unique ID number is assigned to each USB key, enabling the key to replace or supplement personal passwords. The unique ID of the USB key makes it useful as a notebook computer security device providing theft deterrence. Other uses for the USB keys include Web access control, client token for Virtual Private Network access, replacement for password generator tokens and storage of credentials, certificates and licenses.

[0010] In a news release dated 19 January 1999, Rainbow Technologies, Inc. announce a new line of

USB tokens for VPNs (virtual private networks) which provides end user client authentication to VPNs and enables operator access to secured network equipment. Features of these tokens include "Internet security small enough to fit on a key-ring" and "personalization for the end user". The tokens allow a user to keep personal information in his or her pocket rather than on a hard drive.

[0011] A new "unique per individual" model of its USB based tokens was announced by Rainbow Technologies Inc. on 15 March 1999.

[0012] The disclosures of all publications mentioned in the specification and of the publications cited therein are hereby incorporated by reference.

SUMMARY OF THE INVENTION

[0013] The present invention seeks to provide improved flexibly connectible apparatus and improved methods for using the same.

[0014] There is thus provided, in accordance with a preferred embodiment of the present invention, a user-computer interaction method for use by a population of flexibly connectible computer systems and a population of mobile users, the method including storing information characterizing each mobile user on an FCCS plug to be borne by that mobile user and accepting the FCCS plug from the mobile user for connection to one of the flexibly connectible computer systems and employing the information characterizing the mobile user to perform at least one computer operation.

[0015] Further in accordance with a preferred embodiment of the present invention, at least one computer operation comprises authentication.

[0016] Also provided, in accordance with another preferred embodiment of the present invention, is a an FCCS plug device to be borne by a mobile user, the FCCS plug device including a portable device which mates with a flexibly connectible computer system and comprises a memory and information characterizing the mobile user and stored in the memory accessibly to the flexibly connectible computer system.

[0017] Also provided, in accordance with another preferred embodiment of the present invention, is a population of FCCS plug devices to be borne by a corresponding population of mobile users, the population of FCCS plug devices including a multiplicity of portable devices each of which mates with a flexibly connectible computer system and comprises a memory and information characterizing each mobile user in the population of mobile users and stored, accessibly to the flexibly connectible computer system, in the memory of the FCCS plug device to be borne by the mobile user.

[0018] Additionally provided, in accordance with another preferred embodiment of the present invention, is an FCCS plug device including a mating element operative to mate with a flexibly connectible computer system and a memory connected adjacent the mating

element, thereby to form a portable pocket-size plug, wherein the memory is accessible to the flexibly connectible computer system via the mating element.

[0019] Also provided, in accordance with another preferred embodiment of the present invention, is an FCCS plug device including a mating element operative to mate with a flexibly connectible computer system and a CPU connected adjacent the mating element thereby to form a portable pocket-size plug, wherein the CPU has a data connection to the flexibly connectible computer system via the mating element.

[0020] Further in accordance with a preferred embodiment of the present invention, the FCCS plug device also comprises a CPU connected adjacent the mating element, thereby to form a portable pocket-size plug, wherein the CPU has a data connection to the flexibly connectible computer system via the mating element.

[0021] Still further in accordance with a preferred embodiment of the present invention, at least one computer operation comprises digital signature verification and/or controlling access to computer networks.

[0022] Further in accordance with a preferred embodiment of the present invention, the information characterizing each mobile user comprises sensitive information not stored in the computer system, thereby to enhance confidentiality.

[0023] Also provided, in accordance with another preferred embodiment of the present invention, is a user-computer interaction method for use by a population of flexibly connectible computer systems and a population of mobile users, the method including

storing confidential information not stored by the flexibly connectible computer systems on an FCCS plug to be borne by an individual user within the population of mobile users and accepting the FCCS plug from the mobile user for connection to one of the flexibly connectible computer systems and employing the confidential information to perform at least one computer operation, thereby to enhance confidentiality.

[0024] Preferably the apparatus also includes a microprocessor operative to receive the USB communications from the USB interface, to perform computations thereupon and to provide results of the computations to the data storage unit for storage and/or for encryption and/or for authentication and/or for access control.

[0025] The term "USB port" refers to a port for connecting peripherals to a computer which is built according to a USB standard as described in USB specifications available over the Internet at www.usb.org.

[0026] The term "USB plug" or "USB key" or "USB token" refers to a hardware device whose circuitry interfaces with a USB port to perform various functions.

[0027] The term "smart card" refers to a typically plastic card in which is embedded a chip which interacts with a reader, thereby allowing a mobile bearer of the smart card to interact with a machine in which is installed a smart card reader, typically with any of a network of machines of this type.

[0028] Also provided in accordance with a preferred embodiment of the present invention is an electronic token, which preferably mates with a flexible connection providing port such as the USB port of any computer system such as a PC, laptop, palmtop or peripheral. The electronic token preferably does not require any additional reading equipment. The token may authenticate information and/or store passwords or electronic certificates in a token which may be the size of a domestic house key.

[0029] Preferably, when the token is inserted into a flexible connection providing port, a highly secure "dual factor authentication" process (e.g. "what you have" plus "what you know") takes place in which (a) the electronic token is "read" by the host PCC or network and (b) the user types in his or her personal password for authorization.

[0030] Suitable applications for the electronic token include authentication for VPN, extranet and e-commerce.

[0031] The present invention also seeks to provide improved USB apparatus and improved methods for using the same.

[0032] There is thus provided, in accordance with another preferred embodiment of the present invention, USB key apparatus for interacting with a USB host via a USB port, the USB key apparatus including a portable device configured to fit the USB port, the portable device including a USB interface conveying USB communications to and from a USB host, a protocol translator operative to translate the USB communications from USB protocol, into smart card protocol such as an ISO7816 protocol, and from smart card protocol into USB protocol and a smart card chip operative to perform at least one smart card function such as authentication, encryption, access control and secure memory.

[0033] Also provided, in accordance with another preferred embodiment of the present invention, is USB key apparatus with data storage capabilities, the USB key apparatus including a portable device such as a PCB, configured to fit the USB port, the portable device including a USB interface conveying USB communications to and from a USB host and a data storage unit storing information derived from the USB communications.

BRIEF DESCRIPTION OF THE DRAWINGS

[0034] The present invention will be understood and appreciated from the following detailed description, taken in conjunction with the drawings in which:

Fig. 1 is a simplified block diagram of a USB plug device including a CPU and a non-ISO7816 memory, the USB device being constructed and operative in accordance with a preferred embodiment of the present invention;

Fig. 2 is a simplified block diagram of a USB plug device including a CPU and a ISO7816 memory, the USB device being constructed and operative in accordance with a preferred embodiment of the present invention;

Fig. 3 is an exploded front view of an FCCS plug constructed and operative in accordance with a preferred embodiment of the present invention and implementing the USB plug device of Fig. 1;

Fig. 4 is an exploded view of an FCCS plug constructed and operative in accordance with a preferred embodiment of the present invention and implementing the USB plug device of Fig. 2; and Figs. 5A - 5B pictorially illustrate a user-computer interaction method provided in accordance with a preferred embodiment of the present invention for use by a population of flexibly connectible computer systems and a population of mobile users.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0035] Reference is now made to Fig. 1 which is a simplified block diagram of a flexibly connectible USB plug device including a CPU and a non-ISO7816 memory, the USB device being constructed and operative in accordance with a preferred embodiment of the present invention.

[0036] A particular feature of the USB plug device of Fig. 1 is that it has data storage capabilities and is thus analogous to a memory smart card.

[0037] The USB plug device 10 comprises a PCB 25 which includes a microprocessor or CPU 30 such as a Motorola 6805, Cypress chip or Intel 8051; a USB interface device 40; firmware memory 50 serving the firmware of the microprocessor 30; RAM memory 60 of size sufficient to enable contemplated computations on the part of the microprocessor 30; and user data memory 70 which stores a user's data. Some or all of the USB interface device 40, firmware memory 50 and RAM memory 60 may be within the CPU 30.

[0038] The USB interface device 40 and/or the firmware memory 50 may be integrated inside the microprocessor 30.

[0039] The firmware memory may be any suitable type of memory such as but not limited to ROM, EPROM, EEPROM or FLASH.

[0040] The user data memory 70 typically does not include ISO7816-3 memory and may, for example, comprise any of the following types of memory: I²C, Xi²C, 2/3 wire bus, FLASH.

[0041] As shown, the USB plug device 10 is configured to interact with any USB host 20 such as but not

limited to a personal computer or Macintosh having a USB port. Key-host interaction is governed by a USB protocol such as the USB protocol described in the USB specifications available over the Internet at www.usb.org. USB packets pass between the USB host 20 and the USB interface chip 40. Each packet typically includes the following components:

- a. USB header;
- b. Data to be stored/read on the user's data memory 70, plus additional information required by protocols of the memory chip 70, such as but not limited to the address to store/read the data, the length of data to store/read, and CRC checksum information.
- c. USB footer.

[0042] The flow of data typically comprises the following flow:

[0043] The USB interface chip 40 receives USB packets from the USB host 20, parses the data, and feeds the parsed data to the microprocessor 30. The microprocessor 30 writes the data to, or reads the data from, the firmware memory 50, the RAM 60 or the user's data memory 70, using each memory's protocol.

[0044] In read operation, the microprocessor 30 passes the data to the USB interface chip 40 which wraps the data in USB packet format and passes it to the host 20.

[0045] Fig. 2 is a simplified block diagram of a USB plug device, constructed and operative in accordance with a preferred embodiment of the present invention, which is a one-piece smart card reader and smart card chip preferably providing both secured storage and cryptographic capabilities. The USB plug device of Fig. 2 includes both a CPU and a smart card chip (ICC) memory 170, typically a ISO7816 (T = 0/1) protocol-based chip communicating with the CPU 130 using an ISO7816-3 protocol. The apparatus of Fig. 2 is similar to the apparatus of Fig. 1 except that no separate user's data memory 70 is provided. The size of the RAM 160 is typically at least 262 bytes in order to support the ISO 7816_3 T=0 or T=1 protocols.

[0046] Each packet typically includes the following components:

- a. USB header;
- b. ISO7816-3 T=0/1 protocol packet;
- c. USB footer.

[0047] The flow of data in the apparatus of Fig. 2 typically comprises the following flow:

[0048] The USB interface chip 140 gets USB packets from the USB host 120. The USB interface chip 140 parses the data and passes it to the microprocessor 130. The data, which typically comprises a ISO7816-3 T=0/1 formatted packet, is passed by the microprocessor to the smart-card 170 in a ISO7816-3 protocol. The

microprocessor 130 gets the response from the smart card 160 and passes the data to the USB interface chip 140. The USB interface chip 140 wraps the data in USB packet format and passes it to the host 120.

[0049] A particular advantage of the embodiment of Fig. 2 is that smart card functionality is provided but there is no need for a dedicated reader because the plug 110 is connected directly to a USB socket in the host 120.

[0050] The invention shown and described herein is particularly useful for computerized systems serving organizations which process sensitive information such as banks, insurance companies, accountants and other commercial organizations, and professional organizations such as medical or legal organizations.

[0051] Conventional computer systems include a computer (comprising a motherboard) and at least one peripherals. The computer has a number of different ports which respectively mate with the ports of the various peripherals. Each port typically can mate with only certain peripherals and not with other peripherals. For example, the keyboard cannot be connected to the computer via the computer's printer port.

[0052] In state of the art computer systems, also termed herein "flexibly connectible computer systems", the computer and the peripherals each include at least one identical ports having mating ports on any other computer and any other peripheral such that any peripheral can be selectably connected to any computer or to any other peripheral. Also, a peripheral may be connected to the computer not directly as in conventional systems but rather via another peripheral. There is generally always a port available on one or more connected peripherals in an existing computer system such that another peripheral can generally always be connected to an existing computer system.

[0053] One example of a flexibly connectable computer system is a USB (universal standard bus) system in which the computer and each peripheral includes a USB port. Another example of a flexibly connectable computer system is the recently contemplated Firewire system.

[0054] A "USB plug" is a portable device which mates with a USB system and, as opposed to peripherals which contain mechanical elements, typically comprises only memory and/or CPU and therefore is typically pocket-size. More generally, a USB plug is an example of a plug which can be plugged into a flexibly connectible computer system (FCCS).

[0055] The term "FCCS plug" is used herein to refer to a portable device which mates with a flexibly connectible computer system and, as opposed to peripherals which contain mechanical elements, typically comprises only memory and/or CPU and therefore is typically pocket-size. It is appreciated that because each peripheral connected onto a flexibly connectible computer system typically has at least one port, therefore, a flexibly connectible computer system of any configuration typi-

cally has at least one vacant port available to interact with an FCCS plug. USB tokens and Rainbow tokens are both examples of FCCS plugs.

[0056] Typically, each of the plurality of computer system units (computer and one or more peripherals) forming a computer system has at least two identical female sockets and these are interconnected by means of male-male cables. In this embodiment, the FCCS plug may comprise a male socket. However, it is appreciated that any suitable mating scheme may be employed to mate the computer system units and the the FCCS plug of the present invention.

[0057] A known use for FCCS plugs is use in conjunction with software having plug-recognizing capability. Aladdin and Rainbow both market software which is operative only if the host computer system in which a particular software copy resides has plugged into it an FCCS plug which is recognized by the software copy. The Aladdin and Rainbow plugs are not used for authentication.

[0058] Computer systems are often used to receive information characterizing a mobile user, who is one of a population of mobile users, and to process this information. Such information may comprise user identity authentication information, banking information, access rights information, etc. Conventionally, this information is stored on a smart card which is borne by the user and is presented to the computer system by him. However this requires the computer system to be equipped with a smart card reader, a special piece of equipment dedicated to reading the smart card.

[0059] According to a preferred embodiment of the present invention, information characterizing a mobile user is stored on an FCCS plug. Particular advantages of this embodiment of the present invention is that the information is easily borne by the user, on a pocket-size substrate, that any flexibly connectible computer system of any configuration is typically capable of interacting with the user via the FCCS plug, and that no dedicated equipment is required by the computer in order to carry out the interaction.

[0060] Reference is now made to Fig. 3 which is an exploded front view of an FCCS plug constructed and operative in accordance with a preferred embodiment of the present invention and implementing the USB key device of Fig. 1. As shown, the FCCS plug of Fig. 3 comprises a housing typically formed of two snap-together planar cover elements 200 and 210, between which reside a USB connector 220 and the PCB 25 of Fig. 1. The USB connector 220 may, for example comprise a USB PLUG SMT (ACN-0213) device marketed by Aska Technologies Inc., No. 15, Alley 22, Lane 266, Fu Teh, 1st Rd., Hsi Chih, Taipei Shien, Taiwan. The PCB 25 bears the elements 30, 40, 50, 60 and 70 of Fig. 1. Firmware managing the memory 240 may reside on the USB interface controller 230.

[0061] Reference is additionally made to Fig. 4 which is an exploded view of an FCCS plug constructed

and operative in accordance with a preferred embodiment of the present invention and implementing the USB key device of Fig. 2. As shown, the FCCS plug of Fig. 4 comprises a housing typically formed of two snap-together planar cover elements 200 and 210, between which reside the USB connector 220 and a PCB 125. The PCB 125 bears the elements 130, 140, 150, 160 and 170 of Fig. 2. Firmware managing the smart card chip 250 may reside on the USB interface controller 230.

[0062] Smart card functionalities which are preferably provided by the FCCS plug of the present invention include:

1. Controlling access to computer networks: Smart card or plug has ID information, network authenticates and allows access on that basis. Authentication may be based upon "what you have", "what you are" e.g. biometric information and "what you know" (e.g. password).
2. Digital signatures or certificates for verifying or authenticating the identity of the sender of a document.
3. Storage of confidential information e.g. medical information. A smart card or plug may store confidential information and interact with a network which does not store the confidential information.

[0063] Figs. 5A - 5B pictorially illustrate a user-computer interaction method provided in accordance with a preferred embodiment of the present invention for use by a population of flexibly connectible computer systems 300 and a population of mobile users. Information characterizing each mobile user, e.g. name and ID, is loaded into the memory of an FCCS plug 310 to be borne by that mobile user, typically via a USB interface controller such as unit 230 of Fig. 3.

[0064] The plug can then be connected to one of the flexibly connectible computer systems and the information characterizing the mobile user employed to perform at least one computer operation typically comprising a conventional smart card functionality such as authentication.

[0065] Features of a preferred embodiment of the present invention are now described:

a. The need for enhanced user authentication

[0066]

- * Authentication is the basis for any information security system. The ability to authenticate local and remote users is a critical issue for any LAN/Intranet, multi-user environment

b. The need for encryption and confidentiality

[0067]

- * Content encryption & confidentiality becomes an important issue for both the corporation and the individual users

c. The need for password and Sign-On security

[0068]

- * Password security and user password management are key issues for network corporate users. Passwords represent the single most important security concern in any computing environment

[0069] There is a need today for hardware-based PC security tokens

- * Sign-On-Key (SOK) is a hardware-based token that seamlessly integrates with Operating Systems & Applications to provide:

- a user authentication key
- a basis for encryption system
- better Sign-On security and enhanced user password management
- Software Security

Authentication - 3 Basic Elements

[0070]

- * Something you know --> Password
- * Something you have --> Sign-On-Key
- * Something you are --> e.g., Bio-metrics
- * Assumption: Two out of the above three provide "good-enough" security.

Encryption

[0071]

- * The need to encrypt data, files, disks and information flow is evident.
- * An hardware-based token with cryptographic abilities can enhance security and ease-of use.

Sign-On - Where are Passwords used?

[0072]

- * Log on to your O/S
- * Log on to your Network (Local, Remote)
- * Log on to the Internet/ISP
- * Log on to protected Web pages
- * Log on to Group Ware/Communications applica-

tions

- * Log on to other sensitive password-protected applications
- * MS Office & other protected files
- * PC Boot protection (Bios Password)

Sign-On - Major Security Risks

The Sign-On Process

[0073] The Sign-On-Key is a security hardware token, linked by the user to the required applications. Once installed the -Sign-On-Key becomes a part of the log-on process. Sign-On-Key provides the user with many security and other functional benefits.

What Can Sign-On-Key Do For a User?

[0074]

* Sign-On Security

- Enhance security & authentication. The Sign-On-Key is required in addition to the user password

* Sign-On Simplicity

- Simplify log-on process and eliminate the need for a password. The Sign-On-Key replaces the password

* Password Automatic Re-verification

- Check for Sign-On-Key periodically

* Single-Sign-On

- One Sign-On-Key replaces several passwords for several applications

* Mobility & Remote Computing

- Sign-On-Key identifies remote users
- Sign-On-Key can be used as a data secure container
- Theft deterrent of mobile PCs

* General Purpose Security Token

- File & data Encryption
- Authentication
- Certificate Key Holder

Sign-On-Key Various Options

[0075]

- * Several hardware devices may operate as Sign-On-Keys:

- Sign-On-Key USB - A small key that connects to the new standard USB port. USB ports are becoming the new connectivity standard for PCs and Macintosh

- Sign-On-Key SC - A smart card based Sign-On-Key. Can be used with any standard smart card drive

Sign-On-Key USPs & Advantages

[0076]

- * Simple, intuitive, easy to use, attractive token
- * The key IS the token IS the connector
- * Low cost
- * High security
- * High functionality

- Memory inside token
- Processing power
- Automatic Password Re-verification
- Multi token connectivity

* The Agents' solution

Sign-On-Key Architecture

Full Blown System.

Sign On Agents

[0077]

- * The Sign-On-Agent is a software interface between the Sign-On-Key and the application.
- * The Sign-On-Boot is a special interface for the PC boot password.
- * Agents may be provided for:
 - OS/Net Ware - e.g., Windows NT, 95/98, 3x, Novell, Unix
 - Group Ware/Mail - e.g., Lotus Notes, Outlook, Eudora,
 - Enterprise Applications - e.g., SAP, Baan, MK, Oracle, Magic
 - Web Browsers - e.g., Explorer, Navigator

The Most Trivial Agent - Windows NT

[0078]

- * The most trivial Agent will replace the Windows Login session
- * By doing so Users may gain
 - Windows Login Extra security
 - Windows Login simplification (Sign-On-Key replaces password)

Sign-On-Key Web Browsers' Agent/System

[0079]

- * Sign-On-Key can be used as an authentication token to monitor access to secured web pages
- * Web content providers need to authenticate, manage and provide access to their customers

Sign-On-Key API (SDK)

[0080]

- * Sign-On-Key API is the interface level between the Sign-On-Key and 3rd parties' applications.
- * This API may be published and opened for usage by certification providers, security companies and SSO companies.
- * The Sign-On-Key API will also provide encryption & protected memory storage services
- * Sign-On-Key API may be PKCS #11 based/compatible

The Sign-On Process (No CA)

[0081]

- * Installation
 - User installs Agents for required applications
 - User defines Sign-On Parameters for each application
 - User stores Sign-On information in Sign-On-Key
- * Sign-On
 - Application is started
 - Application reaches its Sign-On dialog
 - Application communicates with the Sign-On-Key
 - Sign-On permission is granted based on Sign-On-Key

Sign-On-Key As a Secure Container

[0082]

- * In addition to unique Key ID, Sign-On-Key will contain personal protected memory area
- * This memory area can be used for storing sensitive information and Certificates
- * Applications' ID keys like Lotus Notes ID file or PGP keys can be stored in this memory
- * Doing so - Sign-On-Key can be used to increase mobile computing security. Files IDs are stored in Sign-On-Key instead of disk

15 Sign-On-Key An Encryption Engine & Sign-On-Key Crypt

[0083]

- * Sign-On-Key can be used as an encrypting device
- * An encryption API may be provided, e.g., a 100% smart card compatible Sign-On-Key implementation
- * Sign-On-Key Crypt is a Data/File/Hard disk encryption utility based on Sign-On-Key.

Sign-On-Key Certification Toolkit

[0084]

- * SOK may use PKCS #11 and X509 and store certificates and/or digital IDs.

Sign-On-Key comprises:

[0085]

- * Sign-On-Key USB Token
- * HASP
- * Hardlock
- * Initial Sign-On-Key functionality (Unique ID, personal protected memory)
- * Sign-On-Key USB extension cable
- * Sign-On-Key Smart Card Token
- * Sign-On-Key API (PKCS #11 compliant)
- * Entrust compatibility/link
- * Windows NT Agent
- * Navigator and/or Explorer Agent (S/Mime)
- * Key Plus Crypt (Beta release)
- * Secure Screen Saver
- * Initial marketing package
- * USB proliferation & Windows 98/NT availability are key issues
- * In the US, Germany & Israel all new PCs shipped are USB equipped.
- * Section in Early Development stage.
- * Security Dynamics, ActivCard & Vasco control the market with 1st generation time-based, one-time

password or challenge-based tokens

- * security vendors will look to expand their market share with second generation integrated smart card offerings which will support cryptography, digital signature storage and processing activity

USB: The Better Connection

[0086]

- * Almost unlimited port expansion
- * No add-in cards for new peripherals
 - no setting of IRQs, DMAs, etc.
- * One connection type (plug and port)
 - variety of peripherals
 - no more guesswork
 - simple setup, just plug in and go

USB: The Better Connection

[0087]

- * Addresses need for speed, multimedia
 - 12 Mb/s, Asynch (bulk) & Isoch (real time) data
 - stereo-quality digital audio
 - high frame-rate video (with compression)
 - high latency applications (force-feedback)
- * No power bricks with many new peripherals
 - USB supplies up to 500mA
- * PC User experience is vastly improved
 - Fewer returns and increased sales potential

[0088] It is appreciated that USB is only one example of a flexible connectivity standard and the present invention is not intended to be limited to USB.

[0089] It is appreciated that the software components of the present invention may, if desired, be implemented in ROM (read-only memory) form. The software components may, generally, be implemented in hardware, if desired, using conventional techniques.

[0090] It is appreciated that various features of the invention which are, for clarity, described in the contexts of separate embodiments may also be provided in combination in a single embodiment. Conversely, various features of the invention which are, for brevity, described in the context of a single embodiment may also be provided separately or in any suitable subcombination.

[0091] It will be appreciated by persons skilled in the art that the present invention is not limited to what

has been particularly shown and described hereinabove. Rather, the scope of the present invention is defined only by the claims that follow:

[0092] Where technical features mentioned in any claim are followed by reference signs, those reference signs have been included just for the sole purpose of increasing intelligibility of the claims and accordingly, such reference signs do not have any limiting effect on the scope of each element identified by way of example by such reference signs.

Claims

1. A user-computer interaction method for use by a population of flexibly connectible computer systems and a population of mobile users, the method comprising:

storing information characterizing each mobile user on an FCCS plug to be borne by that mobile user; and

accepting the FCCS plug from the mobile user for connection to one of the flexibly connectible computer systems and employing the information characterizing the mobile user to perform at least one computer operation.

2. A method according to claim 1 wherein said at least one computer operation comprises authentication.
3. An FCCS plug device to be borne by a mobile user, the FCCS plug device comprising:

a portable device which mates with a flexibly connectible computer system and comprises a memory; and information characterizing the mobile user and stored in said memory accessibly to the flexibly connectible computer system.

4. A population of FCCS plug devices to be borne by a corresponding population of mobile users, the population of FCCS plug devices comprising:

a multiplicity of portable devices each of which mates with a flexibly connectible computer system and comprises a memory; and information characterizing each mobile user in the population of mobile users and stored, accessibly to the flexibly connectible computer system, in the memory of the FCCS plug device to be borne by said mobile user.

5. An FCCS plug device comprising:

a mating element operative to mate with a flexibly connectible computer system; and a memory connected adjacent said mating ele-

ment, thereby to form a portable pocket-size plug, wherein the memory is accessible to the flexibly connectible computer system via said mating element.

6. An FCCS plug device comprising:

a mating element operative to mate with a flexibly connectible computer system; and
a CPU connected adjacent said mating element, thereby to form a portable pocket-size plug, wherein the CPU has a data connection to the flexibly connectible computer system via said mating element.

7. An FCCS plug device according to claim 5 and also comprising a CPU connected adjacent said mating element, thereby to form a portable pocket-size plug, wherein the CPU has a data connection to the flexibly connectible computer system via said mating element.

8. A method according to claim 1 wherein said at least one computer operation comprises digital signature verification.

9. A method according to claim 2 wherein said at least one computer operation comprises controlling access to computer networks.

10. A method according to claim 1 wherein said information characterizing each mobile user comprises sensitive information not stored in said computer system, thereby to enhance confidentiality.

11. A user-computer interaction method for use by a population of flexibly connectible computer systems and a population of mobile users, the method comprising:

storing confidential information not stored by the flexibly connectible computer systems on an FCCS plug to be borne by an individual user within said population of mobile users; and
accepting the FCCS plug from the mobile user for connection to one of the flexibly connectible computer systems and employing the confidential information to perform at least one computer operation, thereby to enhance confidentiality.

12. USB key apparatus for interacting with a USB host via a USB port, the USB key apparatus comprising:

a portable device configured to fit the USB port, the portable device comprising:

a USB interface conveying USB communi-

cations to and from a USB host;

a protocol translator operative to translate the USB communications from USB protocol into smart card protocol and from smart card protocol into USB protocol; and
a smart card chip operative to perform at least one smart card function.

13. USB key apparatus according to claim 12 wherein the smart card protocol comprises an ISO7816 protocol.

14. USB key apparatus with data storage capabilities, the USB key apparatus comprising:

a portable device configured to fit a USB port, the portable device comprising:

a USB interface conveying USB communications to and from a USB host; and
a data storage unit storing information derived from the USB communications.

15. Apparatus according to claim 12 wherein the smart card function comprises at least one function selected from the group consisting of secured memory, authentication, encryption and access control.

16. Apparatus according to claim 14 and also comprising a microprocessor operative to receive said USB communications from the USB interface, to perform computations thereupon and to provide results of the computations to the data storage unit for storage.

17. A method for interacting with a USB host via a USB port, the method comprising:

configuring a portable device to fit the USB port;
conveying USB communications to and from a USB host;
translating the USB communications from USB protocol into smart card protocol and from smart card protocol into USB protocol; and
providing a smart card chip operative to perform at least one smart card function.

18. A method according to claim 17 wherein the smart card protocol comprises an ISO7816 protocol.

19. A data storage method comprising:

configuring a portable device to fit a USB port;
conveying USB communications to and from a USB host; and
storing information derived from the USB com-

munications.

20. A method according to claim 17 wherein the smart card function comprises at least one function selected from the group consisting of secured memory, authentication, encryption and access control. 5
21. A method according to claim 19 and also comprising employing a microprocessor to receive said USB communications from the USB interface, to perform computations thereupon and to provide results of the computations to the data storage unit for storage. 10

15

20

25

30

35

40

45

50

55

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5A





FIG. 5B





(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:
02.08.2000 Bulletin 2000/31

(51) Int. Cl.⁷: **G06F 1/00**

(43) Date of publication A2:
17.05.2000 Bulletin 2000/20

(21) Application number: 99120094.0

(22) Date of filing: 21.10.1999

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 10.11.1998 US 189960
05.10.1999 US 412292

(71) Applicant:
Aladdin Knowledge Systems Ltd.
Tel Aviv 67211 (IL)

(72) Inventors:
• **Margalit, Yanki**
Ramat Gan 52223 (IL)
• **Margalit, Dany**
Ramat Gan 52223 (IL)
• **Kastershtien, Rami**
Tel Aviv 67442 (IL)

(74) Representative:
Modiano, Guido, Dr.-Ing. et al
Modiano, Josif, Pisanty & Staub,
Baaderstrasse 3
80469 München (DE)

(54) **A user-computer interaction method for use by flexibly connectable computer systems**

(57) A user-computer interaction method for use by a population of flexibly connectable computer systems and a population of mobile users, the method comprising storing information characterizing each mobile user on an FCCS plug to be borne by that mobile user; and accepting the FCCS plug from the mobile user for connection to one of the flexibly connectable computer systems and employing the information characterizing the mobile user to perform at least one computer operation.

FIG. 1





FIG. 5B





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 99 12 0094

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	WO 94 10773 A (INTELLIGENT SECURITY SYST ;HEPTIG JOHN P (US); BAKER ROBERT (US);) 11 May 1994 (1994-05-11)	1-7,9-11	G06F1/00
A	* page 2, line 25 - page 3, line 19 * * page 4, line 1 - line 16 * * page 9, line 21 - page 10, line 7 * * page 25, line 20 - line 26; figures 1A,1B,3 *	8,12-21	
X	"WIBU-KEY, User's Guide Version 2.50". 'Online! July 1998 (1998-07), WIBU-SYSTEMS AG, KARLSRUHE, GERMANY XP002139279 Retrieved from the Internet: <URL: ftp://www2.wibu.de/pub/download/us/UG250US.pdf> 'retrieved on 2000-05-25!	3,5-7, 14,16, 19,21	
Y	* page 12, paragraph 1 - page 14, paragraph 3 * * page 16, paragraph 2 * * page 25, line 1 - page 27, last line * * page 164 *	12,15, 17,20	
Y	GUEULLE P: "UN DONGLE A PUCE DE TELECARTE" ELECTRONIQUE RADIO PLANS,FR,SPE, PARIS, no. 528, 1 November 1991 (1991-11-01), pages 75-78, XP000266390 ISSN: 1144-5742	12,15, 17,20	G06F
A	* page 76, left-hand column, paragraph 8 - page 77, right-hand column, paragraph 3; figure 1 *	13,18	
A	EP 0 848 315 A (COMPAQ COMPUTER CORP) 17 June 1998 (1998-06-17) * column 6, line 16 - line 47; figure 1 *	1-21	
		-/--	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 31 May 2000	Examiner Moens, R.
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03 82 (P04031)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 12 0094

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	EP 0 554 164 A (GEMPLUS CARD INT) 4 August 1993 (1993-08-04) * abstract; figure 1 *	12, 17	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 31 May 2000	Examiner Moens, R
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons</p> <p>& : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/82 (P04001)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 12 0094

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

31-05-2000


Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9410773 A	11-05-1994	US 5377269 A	27-12-1994
		AU 5543094 A	24-05-1994
		EP 0692166 A	17-01-1996
EP 0848315 A	17-06-1998	CN 1195818 A	14-10-1998
		SG 55422 A	21-12-1998
EP 0554164 A	04-08-1993	FR 2686998 A	06-08-1993
		DE 69308336 D	10-04-1997
		ES 2098688 T	01-05-1997
		JP 6020119 A	28-01-1994
		SG 48082 A	17-04-1998
		US 5420412 A	30-05-1995



dream home source

Front Rendering

Plan #1131



COPYRIGHT © 2004, DREAM HOME SOURCE, INC.

Order online or call now to purchase your dream home plan! 1-800-447-0027

6600 SW 92nd Avenue, Suite 180, Portland, Oregon 97223


www.dreamhomesource.com



dream home source

Main Floor

Plan #1131



COPYRIGHT © 2004, DREAM HOME SOURCE, INC.


Order online or call now to purchase your dream home plan! 1-800-447-0027



dream home source

Second Floor

Plan #1131



COPYRIGHT © 2004, DREAM HOME SOURCE, INC.

Order online or call now to purchase your dream home plan! 1-800-447-0027



dream home source

Plan Specifications

Plan #1131

2979 total square feet
3 bedrooms
2.5 baths
2 car none garage
69'6" wide x 72'0" deep
Roof height: 24'0"
Exterior wall framing: 2x6
Foundation(s): Slab

Living square feet:
Additional square feet:

Designer Comments:

COPYRIGHT © 2004, DREAM HOME SOURCE, INC.

Order online or call now to purchase your dream home plan! 1-800-447-0027



dream home source

Plan Pricing

Plan #1131

Plan Packages

5 sets of plans	\$ 550.00
8 sets of plans	\$ 595.00
Reproducible media	\$ 695.00
Electronic File	\$ 695.00

Foundations Available

Slab Foundation	\$ 0.00
-----------------	---------

Add-Ons

Mirror Reverse plans	\$ 25.00
Additional plan sets	\$ 35.00
Line rendering	\$ 30.00

Best Price, Best Service Guarantee

Dream Home Source is committed to providing superior service at the lowest possible price. If you should see a plan for a lower price on another company's website, magazine, or CD-ROM that is exactly like the one you found on the Dream Home Source website, CD, or DVD, please call us. We will work with you to beat their current price by 5%.

Best Plans – Best Prices – Best Service.

COPYRIGHT © 2004, DREAM HOME SOURCE, INC.

Order online or call now to purchase your dream home plan! 1-800-447-0027